



Duty Point Overview



Typ: GR35I-ZID.DC.CR
Article number: 116892/A01

This document does not replace the technical product specification. It is intended solely as non-binding guidance regarding the information shown in the table of contents, in particular duty point data, characteristic curves and drawings. It is recommended that the technical product specification be agreed or accepted separately after this document.

Contents

1. Technical Data 3
2. Duty Point Data 4
3. Characteristic Curve 5
4. Drawing 6
5. Connection Diagram 7
6. Deviation List 8

© ZIEHL-ABEGG SE

All rights reserved. Confidential and proprietary document, not to be disclosed or used except in accordance with applicable agreements. No disclosure to third parties, if not expressively agreed by ZA SE.

1. Technical Data

Article number	116892/A01
Type key	GR35I-ZID.DC.CR
Designation	Ventilation unit with impeller with backward curved blades.
Fan design	with D flange
Rated values	3~380-480V 50/60Hz P_{ed} 2.50kW 4.00-3.20A 3100min^{-1} 50°C
Electrical connection	Integrated controller
Conformity	ErP2026-Status: Compliant (complete fan)
ErP Data	Measurement category ErP: A Air flow q_v on Eta opt: 5057 m3/h Pressure increase p_{fs} on Eta opt: 1231 Pa Input power P_1 on Eta opt: 2537 W Efficiency H_{statA}: 71.6 % Efficiency grade: N_{actual} = 77.9 / N_{target} = 64* *ErP 2026
Thermal class	THCL155
Efficiency class	IE5
IO-function	ECblue BASIC-MODBUS
Type PFC integrated	no PFC
Painting rotor	Rotor 1 coatpaint resistance class 1 (L-TI-0596)
Colour rotor	RAL 5002 (ultramarine blue)
Material rotor	Aluminium
Painting impeller	unpainted
Colour impeller	like RAL 5002 (ultramarine blue)
Material blades/impeller	Impeller made of ZAmid
Inlet nozzle	Inlet nozzle with measuring device for volume flow
Mater. inlet nozzle	Inlet nozzle made of galvanised sheet metal
Connection diagram	Connection diagram: AP00001C
Motor protection	integrated active temperature management
Type of protection	IP55
Impregnation	Moisture and hot climate protection
Quality of bearings	ball bearing with long-time lubrication
Labelling UL/CSA	E213826 ZC-155, MK116-0009
Rating plate	1x fixed.
Condens. drain holes	Condensation drain hole rotor open
Special bearing	With grooved ball bearing with O-ring
Direction o.rotation	clockwise seen at rotor.
Fitting pos./intake direction	Fitting position H/Vu/Vo
Weight	21.00 kg
Min. operating temperature	-20°C
Disclaimer CT20/DOE	This product complies with the U.S. DOE fan and blower regulation. Due to CT20 regulations for industrial fans and blowers in California, please verify local compliance with your regional representative.

© ZIEHL-ABEGG SE

All rights reserved. Confidential and proprietary document, not to be disclosed or used except in accordance with applicable agreements. No disclosure to third parties, if not expressively agreed by ZA SE.

2. Duty Point Data

GR35I-ZID.DC.CR (116892/A01)		
Design | Fan Size | Motor Brand		GR-E/D | 355 | ZAbluefin ECblue
SFP Class | SFP Value (sfp)	wspm3	| 0
FEI | FEG		0 | 85
Airflow (qv) | Airflow Mains	m³/h	0 | 0
Static Pressure (psf) | Static Pressure Mains	Pa	0 | 0
Dynamic Pressure	Pa	0
Total Pressure pf	Pa	0
Air Velocity	m/s	0.0
Density	kg/m³	1.16
Temperature	°C	20.00
Nominal Rpm (n) | RPM Percentage | max.(nmax)	1/min	0 @ 0.00% | 3100
System Efficiency, stat. (ηsF,sys) | tot. (ηF,sys)	%	0.0 | 0.0
Eta ERP | ERP Year		80.4% | 2026
Frequency	Hz	50
Voltage	V	
Current	A	0
Suction Acoustics (Lw(A),5)|(Lw,5)	dB(A)|dB	0 | 0
Pressure Acoustics (Lw(A),6)|(Lw,6)	dB(A)|dB	0 | 0
Dimensions (Width x Height x Depth)	mm	500 x 500 x 384
Mass	kg	21.0
Kfactor | Kfactor Grille		140 | 130
Guard Grille		no

This product complies with the U.S. DOE fan and blower regulation. Due to CT20 regulations for industrial fans and blowers in California, please verify local compliance with your regional representative.

Full Octave band


f [Hz]	sum	63	125	250	500	1000	2000	4000	8000	f [Hz]	sum	63	125	250	500	1000	2000	4000	8000
$L_{w,5}$	0	0								$L_{w,6}$	0	0							
$L_{w(A),5}$	0	0								$L_{w(A),6}$	0	0							


© ZIEHL-ABEGG SE


All rights reserved. Confidential and proprietary document, not to be disclosed or used except in accordance with applicable agreements. No disclosure to third parties, if not expressively agreed by ZA SE.


3. Characteristic Curve


Measured in standard nozzle in installation type A according to ISO 5801












© ZIEHL-ABEGG SE

All rights reserved. Confidential and proprietary document, not to be disclosed or used except in accordance with applicable agreements. No disclosure to third parties, if not expressively agreed by ZA SE.

4. Drawing

Article number	116892/A01




Dimensions in mm The illustrations shown make no claim to completeness and are for orientation purposes only.

© ZIEHL-ABEGG SE

All rights reserved. Confidential and proprietary document, not to be disclosed or used except in accordance with applicable agreements. No disclosure to third parties, if not expressively agreed by ZA SE.

5. Connection Diagram

Article number	**116892/A01**



www.ziehl-abegg.com
©ZIEHL-ABEGG SE
All rights reserved.
Confidential and proprietary document.
No unauthorized disclosure.
Authorization will have to be obtained from ZIEHL-ABEGG SE in writing.

Index *index* 003	Änderung *revision* Änderung	Benennung / *title*	Anschlussplan *connection diagram*
Ausgabedatum *issue date*	25.05.2023		
Ersteller *creator*	langm	Zeichnungsnummer / *drawing number*	AP00001C

ZIEHL-ABEGG

© ZIEHL-ABEGG SE

All rights reserved. Confidential and proprietary document, not to be disclosed or used except in accordance with applicable agreements. No disclosure to third parties, if not expressively agreed by ZA SE.

6. Deviation List

No customer specification was available. Please note that ZIEHL-ABEGG does not confirm technical requirements beyond this specification if they are not listed in a list of deviations.ZIEHL-ABEGG can therefore neither guarantee nor prove the suitability of this product for this specific application or the customer's intended use. The customer is responsible for testing and approving the product for its intended use.



The Royal League in ventilation, control and drive technology

Intelligent control technology for any application

ZIEHL-ABEGG system capabilities:Everything from a single source – perfectly matched for optimal performance

Please contact us. We would be pleased to design an individual solution for your requirements.We would like to welcome you on our worldwide exhibitions. Please find our next exhibitions here.

ZIEHL-ABEGG EVENTS

© ZIEHL-ABEGG SE

All rights reserved. Confidential and proprietary document, not to be disclosed or used except in accordance with applicable agreements. No disclosure to third parties, if not expressively agreed by ZA SE.